

DOUBLE VERTICAL SCISSORS

The construction method with multiple scissor systems over each other allows high lift travels with relatively small platform dimensions.

This model is always used where great height differences must be overcome but the installation room is limited.



Type	Lifting capacity kg	Lifting height mm	Closed height mm	Length mm	Width mm	Lifting time sek.	Power kW	Weight kg
2021	500	1100	270	900	650	18	0,37	140
2122	1000	1100	270	900	650	18	0,75	175
2132	1000	1600	375	1300	800	30	0,75	330
2134	1000	1600	375	1300	1000	30	0,75	345
2136	1000	1800	400	1500	900	30	2,20	450
2138	1000	1800	400	1500	1200	30	2,20	480
2140	1000	2150	400	1700	900	38	2,20	520
2142	1000	2150	400	1700	1200	38	2,20	570
2155	1000	2800	400	2000	1200	49	2,20	635
2266	1500	3000	450	2200	1300	50	2,20	1100
2333	2000	1600	400	1300	900	36	2,20	395
2334	2000	1600	400	1300	1000	36	2,20	430
2343	2000	1800	400	1500	900	42	2,20	500
2360	2000	1800	400	1500	1200	42	2,20	515
2353	2000	2150	400	1700	900	55	2,20	545
2363	2000	2150	400	1700	1200	55	2,20	600
2355	2000	2800	400	2000	1200	54	3,00	660
2453	3000	2150	440	1700	1200	65	4,00	750
2463	3000	2150	440	1700	1500	65	4,00	790
2476	3000	3000	600	2500	1300	80	3,00	1500
2485	4000	4500	800	4000	2000	80	7,50	3100